

T ECHNICAL INFORMATION



New Tool

Models No. ▶ 6314D



Description ▶ Cordless Driver Drills

CONCEPTION AND MAIN APPLICATIONS

Model 6214D is 12V 10mm cordless driver drill, which is efficient for driving approx.40mm wood screw and drilling approx.9mm hole in wood. Its brief benefits are ;

- *Compact design
 - *Light weight
 - *Equipped with electric brake
 - *Longer life motor by replacing carbon brushes
- Model 6314D is 13mm version of model 6214D.

Model	Battery	Fast Charger	Plastic Carrying Case
6214/6314DA	1222(Ni-Cd)	No	No
6214/6314DWA	1222(Ni-Cd)	DC1411	Yes
6214/6314DWAE	1222(Ni-Cd)X2	DC1411	Yes
6214/6314DWBE	1222(Ni-MH)X2	DC1411	Yes



► Specifications

Motor			DC 12V magnet,motor
Battery			Battery 1222 Ni-Cd,12V,2.0Ah) Battery 1223 Ni-MH,12V,2.2Ah)
No load speed			High:0-1100rpm Low:0-350rpm
Chuck capacity		6214D	0.8mm(1/32")-10mm(3/8")
		6314D	1.5mm(1/16")-13mm(1/2")
Max.drilling capacities	6214D	Steel	10mm(3/8")
		Wood	24mm(15/16")
	6314D	Steel	13mm(1/2")
		Wood	24mm(15/16")
Max.driving capacities	Wood screw		6.4mm(1/4")x55mm(2-3/16")
	Machine screw,Nut		6mm(1/4")
Setting of fastening torque			16 stages+drill-mode
Declutching torque			0.5-5N-m (0.4-3.6ft-lbs) (5-50Kgf-cm)
Max.fastening torque(drill-mode)	High Speed		7N-m(5.1ft-lbs)(70Kgf*cm)
	Low speed		21N-m(15.2ft-lbs)(210Kgf-cm)
Net weight			1.7Kg(3.2lbs)

► Standard equipment

Philips Bit 2-65 ----- 1 pc.
 Battery Cover ----- 1 pc.
 Set Plate -----1 pc.
 Plastic Carrying Case -----1 pc. (except Model 6214/6314DA)
 <Note>The standard equipment may differ country to country.

► Optional accessories

Drill Bit 1.5,2,3,4,5,6 Drill Bit for wood 9,12,15
 Philips Bit 1-65,2-45,2-65,2-110,2-150,2-250,3-45,3-65,3-110
 Slotted Bit 5-45,5-82,6-70,6.35-45, 8-45,8-70
 Socket Bit 7-55,8-55,10-55
 Foam Polishing Pad 125 Rubber Pad Assembly Wool Bonnet 100
 Battery 1200, 1202, 1202A, 1220, 1222,1233
 Fast Charger DC1411,DC1209 (European countries only)
 Fast Automotive Charger DC1412 Holster

► Features and benefits

See the attached sheet for more information.

The standard equipment for the tools shown may differ from country to country.

<#6214D>


Length:197mm

40mm shorter than Model 6211D

Makita	6211D/6311	237mm
	6213D	233mm

Highest driving capacity
among same class tools
(at driving 4.1x38 screw)

110% of Makita 6211D/6311D




Length:209mm

38mm shorter than Model 6311D

6311D:247mm
6313D:243mm

<#6314D>




<Note> Other features and benefits
are equal to #6214D.

► Fastening torque by setting cance ring

Fastening torque

(ft-lbs)(kgf-cm)[N-m]



16 stages of clutch

Proper fastening torque for machine screw M3 - M6 can set.

Matching surface can be secured for various wood screws and woods.

► Repair

(1) Cautions in assembling

To replace the gear assembly, first disconnect the drill chuck.(If the housing only is disassembled, its no need to disconnect the chuck.) Use care not to miss the compression spring 4 inside the speed change lever since it can be easily jumped out when disassembling.

(2) Cautions in assembling

(a) Assembling of the motor and gear assembly

*As the motor bracket is mounted on the gear assembly for repair, turn the motor bracket counterclockwise(viewed from the motor bracket side) to remove it from the gear assembly.




Figure 1

1) Screw the motor bracket into the motor.

2) Turn the motor assembling parts shown in 1) in clockwise(viewed from the motor bracket side) to assemble them on the gear assembly.




Figure 2

(b) Assembling of the leaf spring

Assemble the leaf spring on the housing L as shown on the figure 3.




Figure 3

(c) Assembling of the speed change lever

- 1) Set the two pieces of compression spring 4 in the speed change lever.
- 2) Assemble the speed change lever assembly on the protrusion of the change lever as shown on the figure 4 while using care that the compression spring 4 may not jump over.




Figure 4

(d) Assembling on the housing

- 1) To assemble the one body of gear assembly and motor etc. on the housing L, place the speed change lever on the position shown on the figure 5.




Figure 5

(e) Assembling of the chuck

- 1) Place the chuck on the spindle face.
- 2) Mount the hexagon rod spanner on the chuck and use the vice to fix them.
- 3) Set to the drill mode, normal turning and low speed.
- 4) Set the full charged battery and securely hold the handle.*1
- 5) Allow the trigger to full speed in about 1 second while no impact is adding.
- 6) Widen the claw of chuck at maximum and then fasten the screw for holding the chuck.

*Insufficiently holding the handle may cause the handle to turn around in locking. This machine is going to turn clockwise.

*The left-handed screw is used.

► **Circuit drawing**

